

SYSTEM 2200

Sliding Doors

The System 2200 high-performance sliding patio door offers superior operation and thermal efficiency, making it an excellent choice for upscale residential renovation and new construction projects. The system is available in white, beige or clay and can be laminated with solid color or wood-grain foils.



Performance Summary

Structural: up to LG-PG65
Acoustical: up to 38 dB
Thermal: down to 0.16*

* based on simulation

- 1 European saddle-rail sash design**
Provides exceptionally smooth, low-friction operation and is easier to clean
- 2 1 3/8" (35 mm) glazing channel**
Accommodates triple glazing, increasing both energy efficiency and acoustical properties
- 3 Interlocking sash**
Enhances structural durability and resistance to air infiltration
- 4 Multiple configurations**
Allow flexibility for X-O, O-X or O-X-X-O configurations and dedicated fixed frame for sidelite and transom
- 5 Internal sill drainage system**
Achieves superior resistance to water leakage
- 6 Low-profile, aluminum-capped sloped sill**
Offers unobstructed building entry with the durability of an anodized aluminum finish
- 7 Steel sash reinforcement**
Creates superior structural rigidity, allowing for installation in light-commercial applications
- 8 Multi-point locking system**
Provides added security and product performance



na.rehau.com/2200